

CPSS Building Product Information Sheet

Version 1.1 - Issued 20/09/24

Product

Product name Perforated Supply Diffuser - Secure

Product type Perforated Ceiling Diffusers

Product Identifiers CPSS

Product description and intended use

- The CPSS Perforated Supply Diffuser Secure is designed for highly secure, heavyduty construction for a medium to high level of security.
- The CPSS has 2mm or 3mm diameter holes for 30% or 40% free area supplied with a 4mm thick aluminium surround. The corners of the CPSS are mitred and welded and the fixings include a 3mm thick aluminium spacers.
- Applications for the CPSS include a ceiling or wall application supply diffuser or return if required.
- Compatible with our premi-aire or sheet metal boxes.
- Exact neck sizes include 300 x 300mm up to 600 x 600mm.

Relevant NZBC clauses

- Clause B2 Durability: Performance B2.3.1 (c) 5 Years
- Clause H1 Energy Efficiency: Performance H1.3.6

Contributions to compliance with NZBC

- B2: The lifespan of the CPSS will vary based on the environment it is installed in. For a standard HVAC installation, the CPSS would provide a durability of a minimum of 5 years. Excessively corrosive or harmful environments or exposure to fire, heat or water will reduce the lifespan of the CPSS.
- **H1:** When installed in a commercial building as a supply diffuser the CPSS must be designed to have a maximum pressure drop of 40Pa.
- **H1:** When installed in a commercial building as a return diffuser the CPSS must be designed to have a maximum pressure drop of 30Pa.

Relevant standards

N/A

Conditions and limitations of use

- The CPSS should be specified by a suitably qualified engineer.
- The CPSS should be installed by a suitably qualified and trained tradesperson.

Warnings and bans

The CPSS is **not** subject to a warning or ban under section 26 of the Building Act 2004.

Installation details and product datasheet

The CPSS product datasheets and installation details can be found on our website.



Maintenance requirements

N/A

Manufacture details

Manufacture location New Zealand

Manufactured by Price Holyoake (NZ) Ltd T/A Holyoake Air

Management Solutions by Price

Manufacturer NZBN9429048831215Manufacturer websiteHolyoake.com

Auckland address for service 67 Greenmount Drive,

East Tamaki, Auckland 2013

Auckland office email Auckland@holyoake.com

Auckland office phone number (09) 274 4144

Wellington address for service 89 Main Road,

Tawa,

Wellington 5028

Wellington office email Wellington@holyoake.com

Wellington office phone number (04) 232 2722

Christchurch address for service 81 Treffers Road,

Wigram,

Christchurch 8042

Christchurch office email Christchurch@holyoake.com

Christchurch office phone number (03) 366 6545

Declaration

Price Holyoake (NZ) Ltd has provided this declaration to satisfy the provisions of Schedule 1(d) of the Building (Building Product Information Requirements) Regulations 2022.

Version History

Version	Created	Approved	Date	Changes from previous document
number	by	by	issued	
V1.0	HF	ST	17/06/24	First issue
V1.1	ST	ST	20/09/24	Updated Christchurch Address and website URL