

PVC Duct Tape

Model 7100WL

PROPERTIES

A high-quality, high quality PVC tape with a water-based adhesive coating. Delivers reliable adhesion and flame-retardant performance while maintaining low VOC and low odour, making it suitable for use in enclosed or occupied spaces. Easy to apply by hand, with excellent colour and drying stability over time.

Typical use: Bundling and securing cable and wire harnesses, and sealing, securing, or joining HVAC ducting.

SIZES & COLOURS

- Width: 45mm
- Length: 20m
- Grey Colour



TECHNICAL DATA

PROPERTY	VALUE	STANDARD
Rated temperature	-25°C to 85°C	LV312
Base material	PVC	-
Adhesive type	Water-based	-
Total thickness	0.10mm ± 0.03mm	DIN EN 1942
Tensile strength	≥15 N/cm	DIN EN 14410
Elongation at break	≥125%	DIN EN 14410
Adhesion to steel	≥1.0 N/cm	DIN EN 1939
Adhesion to backing	≥1.0 N/cm	DIN EN 1939
Flame resistance	Class B	LV312

STORAGE

Store at 20-30°C, relative humidity below 65%, away from direct light. Shelf life: 12 months from date of manufacture.

Values are based on standard test data and are provided as guidance only. Contact Price Holyoake for application-specific advice.